**Doc. Number:**

☐ Tentative Specification
☐ Preliminary Specification
■ Approval Specification

# MODEL NO.: N133BGE
# SUFFIX: M42
# DPN: N34H6

**Customer: Dell**

**APPROVED BY** **SIGNATURE**

**Name / Title**
Note

Please return 1 copy for your confirmation with your signature and comments.

| Approved By | Checked By | Prepared By |
|---|---|---|
| 楊竣傑<br>2012-01-30<br>18:59:43 CST | 曹文彬<br>2011-12-28<br>15:29:51 CST | 歐陽志全<br>2011-12-24<br>10:57:43 CST |

## CONTENTS

## REVISION HISTORY

| Version | Date | Page | Description |
|---|---|---|---|
| 3.0 | Dec, 19, 2011 | All | Approval spec Ver.3.0 was first issued. |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |
| | | | |

# 1. GENERAL DESCRIPTION

## 1.1 OVERVIEW

N133BGE-M42 is a 13.3" (13.3" diagonal) TFT Liquid Crystal Display module with display head concepts and 30 pins LVDS interface. This module supports 1366 x 768 HD mode and can display 262,144 colors. The optimum viewing angle is at 6 o'clock direction.

## 1.2 GENERAL SPECIFICATI0NS

| Item | Specification | Unit | Note |
|---|---|---|---|
| Screen Size | 13.3 diagonal | | |
| Driver Element | a-si TFT active matrix | - | - |
| Pixel Number | 1366 x R.G.B. x 768 | pixel | - |
| Pixel Pitch | 0.2148 (H) x 0.2148 (V) | mm | - |
| Pixel Arrangement | RGB vertical stripe | - | - |
| Display Colors | 262,144 | color | - |
| Transmissive Mode | Normally white | - | - |
| Surface Treatment | Hard coating (3H), AG | - | - |
| Luminance, White | 300 | Cd/m2 | |
| Power Consumption | Total 3.68W (Max.) @ cell 0.8W (Max.), BL 2.88W (Max.) | | (1) |

Note (1) The specified power consumption is under the conditions at VCCS = 3.3 V, Ta = 25 ± 2 ºC, fPWM = 200 Hz, Duty=100% and fv = 60 Hz, whereas black pattern is displayed. Without LED converter transfer efficiency.

# 2. MECHANICAL SPECIFICATIONS

| Item | | Min. | Typ. | Max. | Unit | Note |
|---|---|---|---|---|---|---|
| Module Size | Horizontal (H) | - | 316 | - | mm | (1) |
| | Vertical (V) (without cable) | - | 205 | - | mm | |
| | Thickness (T) | - | NA | - | mm | |
| Active Area | Horizontal | 293.1168 | 293.4168 | 293.7168 | mm | |
| | Vertical | 164.6664 | 164.9664 | 165.2664 | mm | |
| Weight (without A-cover and B-cover) | | - | - | 600 | g | |

Note (1) Please refer to the attached drawings for more information of front and back outline dimensions.

## 2.1 CONNECTOR TYPE




Please refer Appendix Outline Drawing for detail design.
User's connector Part No: GS12401-1011P-9H or equivalent

## 3. ABSOLUTE MAXIMUM RATINGS

### 3.1 ABSOLUTE RATINGS OF ENVIRONMENT

| Item | Symbol | Value | | Unit | Note |
|---|---|---|---|---|---|
| | | Min. | Max. | | |
| Storage Temperature | $T_{ST}$ | -20 | +60 | ºC | (1) |
| Operating Ambient Temperature | $T_{OP}$ | 0 | +50 | ºC | (1), (2) |

Note (1) (a) 90 %RH Max. (Ta <= 40 ºC).

(b) Wet-bulb temperature should be 39 ºC Max. (Ta > 40 ºC).

(c) No condensation.

Note (2) The temperature of panel surface should be 0 ºC min. and 60 ºC max.




### 3.2 ELECTRICAL ABSOLUTE RATINGS

#### 3.2.1 TFT LCD MODULE

| Item | Symbol | Value | | Unit | Note |
|---|---|---|---|---|---|
| | | Min. | Max. | | |
| Power Supply Voltage | VCCS | -0.3 | +4.0 | V | (1) |
| Logic Input Voltage | $V_{IN}$ | -0.3 | VCCS+0.3 | V | |
| System PWM signal input for dimming | PWM_IN | -0.3 | 5 | V | |
| Dynamic backlight control | CABC_EN | -0.3 | 5 | V | (1) |

Note (1) Stresses beyond those listed in above “ELECTRICAL ABSOLUTE RATINGS” may cause permanent damage to the device. Normal operation should be restricted to the conditions described in “ELECTRICAL CHARACTERISTICS”.

# 4. ELECTRICAL SPECIFICATIONS

## 4.1 FUNCTION BLOCK DIAGRAM




## 4.2. INTERFACE CONNECTIONS

PIN ASSIGNMENT

| Pin | Symbol | Description | Remark |
|---|---|---|---|
| 1 | NC | No Connection (Reserve) | |
| 2 | VCCS | Power Supply (3.3V typ.) | |
| 3 | VCCS | Power Supply (3.3V typ.) | |
| 4 | VEDID | DDC 3.3V power | |
| 5 | BIST | Panel self test | Bist |
| 6 | CLKEDID | DDC clock | |
| 7 | DATAEDID | DDC data | |
| 8 | Rxin0- | LVDS differential data input | R0-R5, G0 |
| 9 | Rxin0+ | LVDS differential data input | |
| 10 | VSS | Ground | |
| 11 | Rxin1- | LVDS differential data input | G1~G5, B0, B1 |
| 12 | Rxin1+ | LVDS differential data input | |
| 13 | VSS | Ground | |
| 14 | Rxin2- | LVDS Differential Data Input | B2-B5,HS,VS, DE |
| 15 | Rxin2+ | LVDS Differential Data Input | |
| 16 | VSS | Ground | |
| 17 | RxCLK- | LVDS differential clock input | LVDS CLK |
| 18 | RxCLK+ | LVDS differential clock input | |
| 19 | VSS | Ground | |
| 20 | PWM_IN | System PWM signal input for dimming | |
| 21 | CABC_EN | CABC Enable Input | |

| | | | |
|---|---|---|---|
| 22 | PWM_OUT | Panel PWM signal output to system | |
| 23 | NC | No Connection (Reserve) | |
| 24 | VLED Output | LED driver output | |
| 25 | VLED Output | LED driver output | |
| 26 | NC | No Connection (Reserve) | |
| 27 | LED_CA1 | LED Cathode 1 | |
| 28 | LED_CA2 | LED Cathode 2 | |
| 29 | LED_CA3 | LED Cathode 3 | |
| 30 | LED_CA4 | LED Cathode 4 | |

Note (1) The first pixel is odd as shown in the following figure.




Note (2) The setting of CABC function are as follows.

| Pin | Enable | Disable |
|---|---|---|
| CABC_EN | Hi | Lo or Open |

Hi = High level, Lo = Low level.

Note (3) The $I^2C$ structure of CLKEDID and DATAEDID uses multiple slave device and the device addresses are defined as follows. The EDID part is M24C02-RMC6TG and D-VCOM part is iML7978CL.

| Component | Device Address | | | | | | | |
|---|---|---|---|---|---|---|---|---|
| | B7 | B6 | B5 | B4 | B3 | B2 | B1 | WR |
| EEPROM | 1 | 0 | 1 | 0 | 0 | 0 | 0 | X |
| D-VCOM | 1 | 0 | 0 | 1 | 1 | 1 | 1 | X |

## 4.3 ELECTRICAL CHARACTERISTICS

### 4.3.1 LCD ELETRONICS SPECIFICATION

| Parameter | | Symbol | Value | | | Unit | Note |
|---|---|---|---|---|---|---|---|
| | | | Min. | Typ. | Max. | | |
| Power Supply Voltage | | VCCS | 3.0 | 3.3 | 3.6 | V | (1)- |
| Ripple Voltage | | $V_{RP}$ | - | 50 | - | mV | (1)- |
| CABC_EN Input Voltage | High Level | $V_{IHCABC}$ | 2.3 | - | 3.6 | V | |
| | Low Level | $V_{ILCABC}$ | 0 | - | 0.5 | V | |
| PWM Input Voltage | High Level | $V_{IHCABC}$ | 2.3 | - | 3.6 | V | |
| | Low Level | $V_{ILCABC}$ | 0 | - | 0.5 | V | |
| PWM Input Frequency | | $f_{PWM}$ | 190 | - | 2K | Hz | |
| PWMO Output Voltage | High Level | $V_{IHCABC}$ | 2.0 | - | 2.8 | V | |
| | Low Level | $V_{ILCABC}$ | 0 | - | 0.4 | V | |
| PWM Output Frequency | | $f_{PWM}$ | 190 | - | 2K | Hz | |
| Inrush Current | | $I_{RUSH}$ | - | - | 1.5 | A | (1),(2) |
| Power Supply Current | Mosaic | Icc | - | 170 | 190 | mA | (3)a |
| | Black | | - | 200 | 230 | mA | (3)b |

Note (1) The ambient temperature is Ta = 25 ± 2 ºC.

Note (2) $I_{RUSH}$: the maximum current when VCCS is rising

$I_{IS}$: the maximum current of the first 100ms after power-on

Measurement Conditions: Shown as the following figure. Test pattern: black.



**VCCS rising time is 0.5ms**




Note (3) The specified power supply current is under the conditions at VCCS = 3.3 V, Ta = 25 ± 2 ºC, DC Current and $f_v$ = 60 Hz, whereas a power dissipation check pattern below is displayed.

a. Mosaic Pattern



Active Area

b. Black Pattern

Active Area

### 4.3.3 BACKLIGHT UNIT

Ta = 25 ± 2 ºC

| Parameter | Symbol | Value | | | Unit | Note |
|---|---|---|---|---|---|---|
| | | Min. | Typ. | Max. | | |
| LED Light Bar Power Supply Voltage | $V_L$ | 25 | 28 | 30 | V | (1)(2)(Duty100%) |
| LED Light Bar Power Supply Current | $I_L$ | 91.2 | 96 | 100.8 | mA | |
| Power Consumption | $P_L$ | 2.280 | 2.688 | 3.024 | W | (3) |
| LED Life Time | $L_{BL}$ | 15,000 | - | - | Hrs | (4) |

Note (1) LED current is measured by utilizing a high frequency current meter as shown below :




Note (2) For better LED light bar driving quality, it is recommended to utilize the adaptive boost converter with current balancing function to drive LED light-bar.

Note (3) $P_L = I_L \times V_L$ (Without LED converter transfer efficiency)

Note (4) The lifetime of LED is defined as the time when it continues to operate under the conditions at Ta = 25 ±2 °C and $I_L$ = 20 mA(Per EA) until the brightness becomes ≦ 50% of its original value.

## 4.4 LVDS INPUT SIGNAL TIMING SPECIFICATIONS

### 4.4.1 LVDS DC SPECIFICATIONS

| Parameter | Symbol | Value | | | Unit | Note |
|---|---|---|---|---|---|---|
| | | Min. | Typ. | Max. | | |
| LVDS Differential Input High Threshold | $V_{TH(LVDS)}$ | - | - | +100 | mV | (1), $V_{CM}$=1.2V |
| LVDS Differential Input Low Threshold | $V_{TL(LVDS)}$ | -100 | - | - | mV | (1) $V_{CM}$=1.2V |
| LVDS Common Mode Voltage | $V_{CM}$ | 1.125 | - | 1.375 | V | (1) |
| LVDS Differential Input Voltage | $\|V_{ID}\|$ | 100 | - | 600 | mV | (1) |
| LVDS Terminating Resistor | $R_T$ | - | 100 | - | Ohm | - |

Note (1) The parameters of LVDS signals are defined as the following figures.

**Single Ended**




**Differential**




### 4.4.2 LVDS DATA FORMAT



### 4.4.3 COLOR DATA INPUT ASSIGNMENT

The brightness of each primary color (red, green and blue) is based on the 6-bit gray scale data input for the color. The higher the binary input the brighter the color. The table below provides the assignment of color versus data input.

| Color | | Data Signal | | | | | | | | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | | Red | | | | | | Green | | | | | | Blue | | | | | |
| | | R5 | R4 | R3 | R2 | R1 | R0 | G5 | G4 | G3 | G2 | G1 | G0 | B5 | B4 | B3 | B2 | B1 | B0 |
| | Black | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Red | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Green | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| Basic | Blue | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |
| Colors | Cyan | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| | Magenta | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |
| | Yellow | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| | White | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 | 1 |
| | Red(0)/Dark | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Red(1) | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Gray | Red(2) | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Scale | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : |
| Of | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : |
| Red | Red(61) | 1 | 1 | 1 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Red(62) | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Red(63) | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Green(0)/Dark | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Green(1) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| Gray | Green(2) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| Scale | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : |
| Of | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : |
| Green | Green(61) | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 0 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Green(62) | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Green(63) | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Blue(0)/Dark | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 |
| | Blue(1) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 |
| Gray | Blue(2) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 0 |
| Scale | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : |
| Of | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : | : |
| Blue | Blue(61) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 0 | 1 |
| | Blue(62) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 0 |
| | Blue(63) | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 0 | 1 | 1 | 1 | 1 | 1 | 1 |

Note (1) 0: Low Level Voltage, 1: High Level Voltage

## 4.5 DISPLAY TIMING SPECIFICATIONS

The input signal timing specifications are shown as the following table and timing diagram.

| Signal | Item | Symbol | Min. | Typ. | Max. | Unit | Note |
|---|---|---|---|---|---|---|---|
| DCLK | Frequency | 1/Tc | 50 | 75.44 | 80 | MHz | - |
| DE | Vertical Total Time | TV | 773 | 806 | 1008 | TH | - |
| | Vertical Active Display Period | TVD | 768 | 768 | 768 | TH | - |
| | Vertical Active Blanking Period | TVB | TV-TVD | 38 | TV-TVD | TH | - |
| | Horizontal Total Time | TH | 1448 | 1560 | 1950 | Tc | - |
| | Horizontal Active Display Period | THD | 1366 | 1366 | 1366 | Tc | - |
| | Horizontal Active Blanking Period | THB | TH-THD | 194 | TH-THD | Tc | - |

Note (1) Because this module is operated by DE only mode, Hsync and Vsync are ignored.

**INPUT SIGNAL TIMING DIAGRAM**



## 4.6 POWER ON/OFF SEQUENCE

The power sequence specifications are shown as the following table and diagram.

| Symbol | Value | | | Unit | Note |
|---|---|---|---|---|---|
| | Min. | Typ. | Max. | | |
| t1 | 0.5 | - | 10 | ms | |
| t2 | 0 | - | 50 | ms | |
| t3 | 0 | - | 50 | ms | |
| t4 | 500 | - | - | ms | |
| t5 | 200 | - | - | ms | |
| t6 | 200 | - | - | ms | |
| t7 | 0.5 | - | 10 | ms | |




Note (1) Please don't plug or unplug the interface cable when system is turned on.

Note (2) Please avoid floating state of the interface signal during signal invalid period.

# 5. OPTICAL CHARACTERISTICS

## 5.1 TEST CONDITIONS

| Item | Symbol | Value | Unit |
|---|---|---|---|
| Ambient Temperature | Ta | 25±2 | °C |
| Ambient Humidity | Ha | 50±10 | %RH |
| Supply Voltage | $V_{CC}$ | 3.3 | V |
| Input Signal | According to typical value in "3. ELECTRICAL CHARACTERISTICS" | | |
| LED Light Bar Input Current | $I_L$ | 96 | mA |

The measurement methods of optical characteristics are shown in Section 5.2. The following items should be measured under the test conditions described in Section 5.1 and stable environment shown in Note (5).

## 5.2 OPTICAL SPECIFICATIONS

| Item | | Symbol | Condition | Min. | Typ. | Max. | Unit | Note |
|---|---|---|---|---|---|---|---|---|
| Contrast Ratio | | CR | $\theta_x$=0°, $\theta_Y$ =0° Viewing Normal Angle | 300 | 500 | - | - | (2), (5), (7) |
| Response Time | | $T_R$ | | - | 8 | 12 | ms | (3), (7) |
| | | $T_F$ | | - | 8 | 13 | ms | |
| Average Luminance of White | | $L_{AVE}$ | | 255 | 300 | - | cd/m$^2$ | (4), (6), (7) |
| Color Chromaticity | Red | Rx | | Typ – 0.03 | 0.595 | Typ + 0.03 | - | (1), (7) |
| | | Ry | | | 0.345 | | - | |
| | Green | Gx | | | 0.320 | | - | |
| | | Gy | | | 0.565 | | - | |
| | Blue | Bx | | | 0.155 | | - | |
| | | By | | | 0.139 | | - | |
| | White | Wx | | | 0.313 | | - | |
| | | Wy | | | 0.329 | | - | |
| Viewing Angle | Horizontal | $\theta_x$+ | CR≥10 | 40 | 45 | | Deg. | (1), (5), (7) |
| | | $\theta_x$- | | 40 | 45 | - | | |
| | Vertical | $\theta_Y$+ | | 15 | 20 | - | | |
| | | $\theta_Y$- | | 40 | 45 | - | | |
| White Variation of 5 Points | | $\delta W_{5p}$ | $\theta_x$=0°, $\theta_Y$ =0° | 70 | 80 | - | % | (5), (6), (7) |
| | | $\delta W_{13p}$ | | 60 | 70 | - | % | |

Note (1) Definition of Viewing Angle (θx, θy)




Note (2) Definition of Contrast Ratio (CR):

The contrast ratio can be calculated by the following expression.

Contrast Ratio (CR) = L63 / L0

L63: Luminance of gray level 63

L 0: Luminance of gray level 0

CR = CR (1)

CR (X) is corresponding to the Contrast Ratio of the point X at Figure in Note (6).

Note (3) Definition of Response Time ($T_R$, $T_F$):



Note (4) Definition of Average Luminance of White ($L_{AVE}$):

Measure the luminance of gray level 63 at 5 points

$L_{AVE}$ = [L (1)+ L (2)+ L (3)+ L (4)+ L (5)] / 5

L (x) is corresponding to the luminance of the point X at Figure in Note (6)

Note (5) Measurement Setup:

The LCD module should be stabilized at given temperature for 20 minutes to avoid abrupt temperature change during measuring. In order to stabilize the luminance, the measurement should be executed after lighting Backlight for 20 minutes in a windless room.




Note (6) Definition of White Variation (δW):

Measure the luminance of gray level 63 at 5 points

$\delta W_{5p}$ = {Minimum [L (1)~L (5)] / Maximum [L (1)~ L (5)]}*100%

δW13p = {Minimum [L (1)~L (13)] / Maximum [L (1)~L (13)]}*100%




Ⓧ : Test Point

X=1 to 13

Note (7) The listed optical specifications refer to the initial value of manufacture, but the condition of the specifications after long-term operation will not be warranted.

## 6. RELIABILITY TEST ITEM

| Test Item | Test Condition | Note |
|---|---|---|
| High Temperature Storage Test | 60ºC, 240 hours | (1) (2) |
| Low Temperature Storage Test | -20ºC, 240 hours | |
| Thermal Shock Storage Test | -20ºC, 0.5hour←→60℃, 0.5hour; 100cycles, 1hour/cycle | |
| High Temperature Operation Test | 50ºC, 240 hours | |
| Low Temperature Operation Test | 0ºC, 240 hours | |
| High Temperature & High Humidity Operation Test | 50ºC, RH 80%, 240hours | |
| ESD Test (Operation) | 150pF, 330Ω, 1sec/cycle<br>Condition 1 : Contact Discharge, ±8KV<br>Condition 2 : Air Discharge, ±15KV | (1) |
| Shock (Non-Operating) | 220G, 2ms, half sine wave,1 time for each direction of ±X,±Y,±Z | (1)(3) |
| Vibration (Non-Operating) | 1.5G / 10-500 Hz, Sine wave, 30 min/cycle, 1cycle for each X, Y, Z | (1)(3) |

Note (1) criteria : Normal display image with no obvious non-uniformity and no line defect.

Note (2) Evaluation should be tested after storage at room temperature for more than two hour

Note (3) At testing Vibration and Shock, the fixture in holding the module has to be hard and rigid enough so that the module would not be twisted or bent by the fixture.

# 7. PACKING

## 7.1 MODULE LABEL & CARTON LABEL

The barcode nameplate is pasted on each module as illustration, and its definitions are as following explanation.


(a) Dell 2D label contains information as below:

(a-1) Serial ID: CN-0N34H6-70896-YMD-XXXX-ZZZ

- Serial Numbers
- Production Year, Month, Date
- Manufacturing ID
- Part Number

(a-2) ZZZ :Revision code: X00, X10, X20, A00..etc.

| BUILD PHASE | REVISION |
|---|---|
| SST (WS) | X00,X01,X02,…X09 |
| PT (ES) | X10,X11,X12,…X19 |
| ST (CS) | X20,X21,X23,…X29 |
| XB (MP) | A00,A01,A02,…A99 |

Dell carton label contains information as below:


(a) PKG ID: 04688-70896-YMD-XXXXXX-0N34H6-ZZ

- Dell P/N
- Serial numbers.
- Production Year, Month, Date
- Manufacturing ID

(b) Production location: Made in XXXX.

(c) Revision code: X00, X10, X20, A00..etc.

(d) BOX Quantity :ZZ

## 7.2 CARTON

(1)Box Dimensions: 540(L)*450(W)*320(H)
(2)16 Modules/Carton




**Figure. 7-2 Packing method**

## 7.3 PALLET




**Figure. 7-3 Packing method**

# 8. PRECAUTIONS

## 8.1 HANDLING PRECAUTIONS

(1) The module should be assembled into the system firmly by using every mounting hole. Be careful not to twist or bend the module.

(2) While assembling or installing modules, it can only be in the clean area. The dust and oil may cause electrical short or damage the polarizer.

(3) Use fingerstalls or soft gloves in order to keep display clean during the incoming inspection and assembly process.

(4) Do not press or scratch the surface harder than a HB pencil lead on the panel because the polarizer is very soft and easily scratched.

(5) If the surface of the polarizer is dirty, please clean it by some absorbent cotton or soft cloth. Do not use Ketone type materials (ex. Acetone), Ethyl alcohol, Toluene, Ethyl acid or Methyl chloride. It might permanently damage the polarizer due to chemical reaction.

(6) Wipe off water droplets or oil immediately. Staining and discoloration may occur if they left on panel for a long time.

(7) If the liquid crystal material leaks from the panel, it should be kept away from the eyes or mouth. In case of contacting with hands, legs or clothes, it must be washed away thoroughly with soap.

(8) Protect the module from static electricity, it may cause damage to the C-MOS Gate Array IC.

(9) Do not disassemble the module.

(10) Do not pull or fold the LED wire.

(11) Pins of I/F connector should not be touched directly with bare hands.

## 8.2 STORAGE PRECAUTIONS

(1) High temperature or humidity may reduce the performance of module. Please store LCD module within the specified storage conditions.

(2) It is dangerous that moisture come into or contacted the LCD module, because the moisture may damage LCD module when it is operating.

(3) It may reduce the display quality if the ambient temperature is lower than 10 ºC. For example, the response time will become slowly, and the starting voltage of LED will be higher than the room temperature.

## 8.3 OPERATION PRECAUTIONS

(1) Do not pull the I/F connector in or out while the module is operating.

(2) Always follow the correct power on/off sequence when LCD module is connecting and operating. This can prevent the CMOS LSI chips from damage during latch-up.

(3) The startup voltage of Backlight is approximately 1000 Volts. It may cause electrical shock while assembling with converter. Do not disassemble the module or insert anything into the Backlight unit.

**Appendix. EDID DATA STRUCTURE**

The EDID (Extended Display Identification Data) data formats are to support displays as defined in the VESA Plug & Display and FPDI standards.

| Byte # (decimal) | Byte # (hex) | Field Name and Comments | Value (hex) | Value (binary) |
|---|---|---|---|---|
| 0 | 0 | Header , Fixed | 00 | 00000000 |
| 1 | 1 | Header , Fixed | FF | 11111111 |
| 2 | 2 | Header , Fixed | FF | 11111111 |
| 3 | 3 | Header , Fixed | FF | 11111111 |
| 4 | 4 | Header , Fixed | FF | 11111111 |
| 5 | 5 | Header , Fixed | FF | 11111111 |
| 6 | 6 | Header , Fixed | FF | 11111111 |
| 7 | 7 | Header , Fixed | 00 | 00000000 |
| 8 | 8 | ID system manufacturer name | 0D | 00001101 |
| 9 | 9 | ID system manufacturer name | AE | 10101110 |
| 10 | 0A | ID system Product Code (LSB) | 38 | 00111000 |
| 11 | 0B | ID system Product Code (MSB) | 13 | 00010011 |
| 12 | 0C | 32-bit serial # Unused(01h for VESA, 00h for SPWG) | 00 | 00000000 |
| 13 | 0D | 32-bit serial # Unused(01h for VESA, 00h for SPWG) | 00 | 00000000 |
| 14 | 0E | 32-bit serial # Unused(01h for VESA, 00h for SPWG) | 00 | 00000000 |
| 15 | 0F | 32-bit serial # Unused(01h for VESA, 00h for SPWG) | 00 | 00000000 |
| 16 | 10 | Week of manufacture 1 - 53 (unused: 00h) : 10h fixed by CMN | 30 | 00110000 |
| 17 | 11 | Year of manufacture year - 1990(unsed:00h) : 14h (Year 2011) fixed by CMN | 15 | 00010101 |
| 18 | 12 | Version=1 | 01 | 00000001 |
| 19 | 13 | Revision=4 | 04 | 00000100 |
| 20 | 14 | Vedio Input Definition | 90 | 10010000 |
| 21 | 15 | Active area horizontal 29.341cm | 1D | 00011101 |
| 22 | 16 | Active area vertical 16.496cm | 10 | 00010000 |
| 23 | 17 | Display Gamma (Gamma = ”2.2”) | 78 | 01111000 |
| 24 | 18 | Feature support | 02 | 00000010 |
| 25 | 19 | Rx1, Rx0, Ry1, Ry0, Gx1, Gx0, Gy1, Gy0 | 98 | 10011000 |
| 26 | 1A | Bx1, Bx0, By1, By0, Wx1, Wx0, Wy1, Wy0 | 55 | 01010101 |
| 27 | 1B | Rx = “0.584” | 95 | 10010101 |
| 28 | 1C | Ry = “0.349” | 59 | 01011001 |
| 29 | 1D | Gx = ”0.338” | 56 | 01010110 |
| 30 | 1E | Gy = ”0.574” | 93 | 10010011 |
| 31 | 1F | Bx = ”0.157” | 28 | 00101000 |
| 32 | 20 | By = ”0.126” | 20 | 00100000 |
| 33 | 21 | Wx = ”0.313” | 50 | 01010000 |
| 34 | 22 | Wy = ”0.329” | 54 | 01010100 |
| 35 | 23 | Established timings 1 | 00 | 00000000 |
| 36 | 24 | Established timings 2 (1600x900@60Hz) | 00 | 00000000 |
| 37 | 25 | No manufacturer's specific timing | 00 | 00000000 |
| 38 | 26 | Standard timing ID # 1 | 01 | 00000001 |
| 39 | 27 | Standard timing ID # 1 | 01 | 00000001 |
| 40 | 28 | Standard timing ID # 2 | 01 | 00000001 |

| | | | | |
|---|---|---|---|---|
| 41 | 29 | Standard timing ID # 2 | 01 | 00000001 |
| 42 | 2A | Standard timing ID # 3 | 01 | 00000001 |
| 43 | 2B | Standard timing ID # 3 | 01 | 00000001 |
| 44 | 2C | Standard timing ID # 4 | 01 | 00000001 |
| 45 | 2D | Standard timing ID # 4 | 01 | 00000001 |
| 46 | 2E | Standard timing ID # 5 | 01 | 00000001 |
| 47 | 2F | Standard timing ID # 5 | 01 | 00000001 |
| 48 | 30 | Standard timing ID # 6 | 01 | 00000001 |
| 49 | 31 | Standard timing ID # 6 | 01 | 00000001 |
| 50 | 32 | Standard timing ID # 7 | 01 | 00000001 |
| 51 | 33 | Standard timing ID # 7 | 01 | 00000001 |
| 52 | 34 | Standard timing ID # 8 | 01 | 00000001 |
| 53 | 35 | Standard timing ID # 8 | 01 | 00000001 |
| 54 | 36 | Detailed timing description # 1 Pixel clock (“71.01MHz”, According to VESA CVT Rev1.4) | BD | 10111101 |
| 55 | 37 | # 1 71.01MHz/10000 =7101=1BBD(Hex) | 1B | 00011011 |
| 56 | 38 | # 1 H active (“1366”) | 56 | 01010110 |
| 57 | 39 | # 1 H blank (“132”) | 84 | 10000100 |
| 58 | 3A | # 1 H active : H blank (“1366 : 132”) | 50 | 01010000 |
| 59 | 3B | # 1 V active (”768”) | 00 | 00000000 |
| 60 | 3C | # 1 V blank (”22”) | 16 | 00010110 |
| 61 | 3D | # 1 V active : V blank (”768 :22”) | 30 | 00110000 |
| 62 | 3E | # 1 H sync offset (”48”) | 30 | 00110000 |
| 63 | 3F | # 1 H sync pulse width ("32”) | 20 | 00100000 |
| 64 | 40 | # 1 V sync offset : V sync pulse width (”1 : 4”) | 14 | 00010100 |
| 65 | 41 | # 1 H sync offset : H sync pulse width : V sync offset : V sync width (”48: 32 : 1 : 4”) | 00 | 00000000 |
| 66 | 42 | # 1 H image size (”293 mm”) | 25 | 00100101 |
| 67 | 43 | # 1 V image size (”164 mm”) | A4 | 10100100 |
| 68 | 44 | # 1 H image size : V image size ("293 : 164”) | 10 | 00010000 |
| 69 | 45 | # 1 H boarder (”0”) | 00 | 00000000 |
| 70 | 46 | # 1 V boarder (”0”) | 00 | 00000000 |
| 71 | 47 | Non-interlaced, Normal Display, Digital separate, Positive Hsync, Negative Vsync | 1A | 00011010 |
| 72 | 48 | Detailed timing description # 1 Pixel clock (“47.34MHz”, According to VESA CVT Rev1.4) | 7E | 01111110 |
| 73 | 49 | # 2 47.34MHz/10000 =4734=127E(Hex) | 12 | 00010010 |
| 74 | 4A | # 1 H active (“1366”) | 56 | 01010110 |
| 75 | 4B | # 1 H blank (“132”) | 84 | 10000100 |
| 76 | 4C | # 1 H active : H blank (“1366 : 132”) | 50 | 01010000 |
| 77 | 4D | # 1 V active (”768”) | 00 | 00000000 |
| 78 | 4E | # 1 V blank (”22”) | 16 | 00010110 |
| 79 | 4F | # 1 V active : V blank (”768 :22”) | 30 | 00110000 |
| 80 | 50 | # 1 H sync offset (”48”) | 30 | 00110000 |
| 81 | 51 | # 1 H sync pulse width ("32”) | 20 | 00100000 |
| 82 | 52 | # 1 V sync offset : V sync pulse width (”1 : 4”) | 14 | 00010100 |
| 83 | 53 | # 1 H sync offset : H sync pulse width : V sync offset : V sync width (”48: 32 : 1 : 4”) | 00 | 00000000 |
| 84 | 54 | # 2 H image size (”293 mm”) | 25 | 00100101 |

| | | | | |
|---|---|---|---|---|
| 85 | 55 | # 2 V image size (”164 mm”) | A4 | 10100100 |
| 86 | 56 | # 2 H image size : V image size (”293 : 164”) | 10 | 00010000 |
| 87 | 57 | # 2 H boarder (”0”) | 00 | 00000000 |
| 88 | 58 | # 2 V boarder (”0”) | 00 | 00000000 |
| 89 | 59 | Non-interlaced, Normal Display, Digital separate, Positive Hsync, Negative Vsync | 1A | 00011010 |
| 90 | 5A | Flag | 00 | 00000000 |
| 91 | 5B | Flag | 00 | 00000000 |
| 92 | 5C | Flag | 00 | 00000000 |
| 93 | 5D | Data Type Tag: Alphanumeric Data String (ASCII) | FE | 11111110 |
| 94 | 5E | Flag | 00 | 00000000 |
| 95 | 5F | Dell P/N 1st Character "N" | 4E | 01001110 |
| 96 | 60 | Dell P/N 2nd Character "3" | 33 | 00110011 |
| 97 | 61 | Dell P/N 3rd Character "4" | 34 | 00110100 |
| 98 | 62 | Dell P/N 4th Character "H" | 48 | 01001000 |
| 99 | 63 | Dell P/N 5th Character "6" | 36 | 00110110 |
| 100 | 64 | EDID Revision | 81 | 10000001 |
| 101 | 65 | Manufacturer P/N "1" | 31 | 00110001 |
| 102 | 66 | Manufacturer P/N "3" | 33 | 00110011 |
| 103 | 67 | Manufacturer P/N "3" | 33 | 00110011 |
| 104 | 68 | Manufacturer P/N "B" | 42 | 01000010 |
| 105 | 69 | Manufacturer P/N "G" | 47 | 01000111 |
| 106 | 6A | Manufacturer P/N "E" | 45 | 01000101 |
| 107 | 6B | Manufacturer P/N (If <13 char, then terminate with ASCII code 0Ah, set remaining char = 20h) | 0A | 00001010 |
| 108 | 6C | Flag | 00 | 00000000 |
| 109 | 6D | Flag | 00 | 00000000 |
| 110 | 6E | Flag | 00 | 00000000 |
| 111 | 6F | Data Type Tag: Manufacturer Specified Data 00 | 00 | 00000000 |
| 112 | 70 | Flag | 00 | 00000000 |
| 113 | 71 | Color Management | 00 | 00000000 |
| 114 | 72 | Panel Type and Revision | 41 | 01000001 |
| 115 | 73 | Frame Rate | 31 | 00110001 |
| 116 | 74 | Light Controller Interface and Maximum Luminance | 9E | 10011110 |
| 117 | 75 | Front Surface / Polarizer and Pixel Structure | 00 | 00000000 |
| 118 | 76 | Multi-Media Features | 10 | 00010000 |
| 119 | 77 | Multi-Media Features | 00 | 00000000 |
| 120 | 78 | Special Features | 00 | 00000000 |
| 121 | 79 | Special Feature | 01 | 00000001 |
| 122 | 7A | Special Features | 01 | 00000001 |
| 123 | 7B | (If <13 char, then terminate with ASCII code 0Ah, set remaining char = 20h) | 0A | 00001010 |
| 124 | 7C | (If <13 char, then terminate with ASCII code 0Ah, set remaining char = 20h) | 20 | 00100000 |
| 125 | 7D | (If <13 char, then terminate with ASCII code 0Ah, set remaining char = 20h) | 20 | 00100000 |
| 126 | 7E | No extension | 00 | 00000000 |
| 127 | 7F | Checksum | 3C | 00111100 |

## Appendix. OUTLINE DRAWING

## N133BGE-M42







| | | | |
|---|---|---|---|
| 1 | | | |
| 2 | | | |
| 3 | | | |
| 4 | | | |
| 5 | | | |
| 6 | | | |
| 7 | | | |
| 8 | | | |
| 9 | | | |
| 10 | | | |
| 11 | | | |
| 12 | | | |
| 13 | | | |
| 14 | | | |
| 15 | | | |
| 16 | | | |

| | | | |
|---|---|---|---|
| 17 | | | |
| 18 | | | |
| 19 | | | |
| 20 | | | |
| 21 | | | |
| 22 | | | |
| 23 | | | |
| 24 | | | |
| 25 | | | |
| 26 | | | |
| 27 | | | |
| 28 | | | |
| 29 | | | |
| 30 | | | |
| 31 | | | |
| 32 | | | |
| 33 | | | |
| 34 | | | |
| 35 | | | |




FPC, T-CON Positions.